



Product Change Notice (PCN)

Date: 10/20/2023

PCN Number: PCN-0454909R-01

To Our Customers:

We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: PJ-083H, PJ-083AH, PJ-083BH

Reason(s) for Change: *Manufacturing improvement process*

Description of Change: *Reel Quantity and Material Change*

PREVIOUS CUI DEVICES DETAIL / IMAGE				PREVIOUS CUI DEVICES DETAIL / IMAGE			
	MATERIAL	PLATING		DESCRIPTION	MATERIAL	PLATING/COLOR	
center pin	copper	nickel		center pin	copper	nickel	
terminal 1	brass	silver		terminal 1	brass	silver	
terminal 2	copper alloy	silver		terminal 2	brass	silver	
terminal 3	brass	silver		terminal 3	brass	silver	
shield A	brass	nickel		shield A	brass	nickel	
shield B	stainless steel			shield B	stainless steel		
insulator	PA10T			insulator	PA10T (UL94V-0)		

SPECIFICATIONS				
parameter	conditions/description	min	typ	max units
rated input voltage			24	Vdc
rated input current			5.0	A
contact resistance	between terminal and mating plug		50	mΩ
	between terminal in a closed circuit		30	mΩ
insulation resistance	at 500 Vdc between adjacent contacts	100		MΩ
voltage withstand	for 1 minute, 0.5 mA between adjacent contacts		500	Vdc
insertion/withdrawal force		0.3	3	kg
operating temperature		-25	85	°C
life	at a rate of 24 cycles/minute		5,000	cycles
flammability rating	UL94V-0			
RoHS	yes			

SPECIFICATIONS				
parameter	conditions/description	min	typ	max units
rated input voltage			24	Vdc
rated input current			5.0	A
contact resistance	between terminal and mating plug		50	mΩ
	between terminal in a closed circuit		30	mΩ
insulation resistance	at 500 Vdc	100		MΩ
voltage withstand	for 1 minute		500	Vdc
insertion/withdrawal force		0.5	2	kg
operating temperature		-25	85	°C
life	at a rate of 10-20 cycles		5,000	cycles
flammability rating	UL94V-0			
RoHS	yes			

F-723-001

Revision: A

